

MOUNTING LOCATION:

Right Side of Radio JR

TOOLS REQUIRED:

Phillips screwdriver

Dash tool, T-20 Torx Driver

HARDWARE INCLUDED:

(3) A - #8X9/16 Needle Point Screw

75001 TOP W/(2)-O- 8/32" Acorn Nuts

CELL PHONE & MEDIA MOUNT

INSTALLATION INSTRUCTIONS

PART#: **751311508**

MFG: **NISSAN**

MODELS & YEARS:

Rogue 2008-2011 & 12-13

Rogue Select 14-15

** ADVISEMENT **

Read instructions completely prior to starting installation. All InDash Mounts are designed so that after installation, phone is facing normal driver position for left-hand drive vehicles. This mount is not designed to be used in foreign countries with right-hand drive vehicles. Use extreme care when working around the plastic components on the dash. Excess force, can cause breakage of the plastic components.

STEP #1: 2008-2011: With Dash Tool, remove shifter bezel by lifting up releasing (4) clips. **2012:** With Dash Tool remove the top of dash speaker cover starting at the front by the windshield. **ALL:** Safely move shifter into D. Then use dash tool to remove climate control bezel by inserting tool into side of bezel and pry out to release (4) clips. Set bezel aside. Remove (2) screws from under the radio.

STEP #2: With dash tool, release air vent bezel, starting at the bottom sides prying to release (1) clip each side. **08-11:** Continue up to release (4) more clips, and pull up and out to release complete bezel. **12-15:** With Phillips screwdriver remove the (4) screws that hold the speaker in place. Remove the speaker, disconnect the plug and set aside. Continue to release bezel working your way up to just beside the radio by releasing (4) clips. Grasp the bezel at the sides and pull out towards you to release (4) more clips. Lift out bezel enough to get at radio screws.

STEP #3: Remove the (4) radio screws and pull the radio out just enough to get at the T-20 Torx screws of the radio bracket. Remove the (2) radio bracket screws with Phillips screwdriver or T-20 Torx. Install bottom piece of InDash by PanaVise Mount over screw holes (and/or under the bracket) and reinstall the (2) screws. Replace the bezels and speaker starting at the bottom, tilting it into place.

STEP#4: Install the top part of InDash by PanaVise Mount with the (2) Acorn nuts.

STEP#5: Replace the bezels, speaker, and climate control in reverse order.

INSTALLATION IS NOW COMPLETE, ENJOY YOUR NEW INDASH BY PANAVISE MOUNT!



Shifter bezel Removal (08-11 only)



Climate Control Removal (All)



Air Vent Removal (08-11 only)



Bottom Piece Installed (over)



InDash Installed Showing Location 08-11



InDash Installed Showing Location 12-15

08-01-16

